



D5518-1 CROSSBOLT SPACER

NOTES:
1) MATERIAL: Ø 0.375 X 0.058 WALL 6061-T4/-T42 ALUMINUM TUBING PER WW-T-700/6, AMS 4081, OR ASTM B210/B221/B241
REF DART SPEC M6061T4T0.375W.058
OR
Ø 0.375 X 0.058 WALL 6061-T6/-T62/-T6510/-T6511 ALUMINUM TUBING PER WW-T-700/6, QQ-A-200/8, QQ-A-225/8, AMS 4080/4082/4083,
OR ASTM B210/B221/B241
REF DART SPEC M6061T6T0.375W.058
HEAT TREAT TO -T4/-T42 CONDITION. MIN UTS = 30 KSI (60 HREW MIN)
2) FINISH: NONE
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: NONE
7) WEIGHT: 0.02 lbs

PRELIMINARY ISSUE

A	NEW ISSUE		NO	17.02.24
REV.	DESCRIPTION		BY	DATE
DESIGN	NO	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
DRAWN	NO			
CHECKED	CP	DRAWING NO.		REV. A4
MFG. APPR.	DP	D5518		SHEET 1 OF 1
APPROVED		TITLE		SCALE
DE APPR.		CROSSBOLT SPACER		NTS
DATE	17.02.24	COPYRIGHT © 2017 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>		